

Panther 56 Diesel Pump

730000



- 230v diesel transfer pump
- 56lpm
- 1" inlet and outlet
- On/Off Switch



BP3000 Diesel Pump Kit

225410 (12v) / 226380 (24v)

- Pump c/w 2m cable & clips
- Manual Self 2000 nozzle
- 4m x 3/4" hose & foot valve c/w strainer
- Max flow rate of 50lpm
- Available in 12v or 24v

Goldenrod Fuel Filter

CTJ1800 (Particle) / CTJ1809 (Water)

- Particle or particle/water filters
- 60lpm—suitable for gravity fed and low flow pumping systems
- 10µ particle, 15µ particle/water
- 1" F BSP inlet and outlet



Self 2000 Manual Diesel & Oil Nozzle

641000 / 656000

- Max flow rate 120 lpm
- Max pressure 5 bar
- 25mm spout OD
- 1" F BSP Swivel (641000) or 1" Hose Tail (656000)



Gravity Hose Kit

OAB3350



- 3m 1" swaged m x m diesel hose
- Manual nozzle, locking angle valve and PTFE tape
- Steel hose tails and ring clamps

K33 Fuel Flow Meter

553000


- 3 digit mechanical diesel meter
- 1" F BSP inlet and outlet ports
- Body can be rotated to allow flow from 4 directions



Cim Tek Diesel Fuel Filter

CTH1830

- Water & Particle Filter
- 68 lpm, 10µ
- 1" F BSP Flanged
- 1 Head, 1 Element



Automatic Fuel Nozzle

603060



- Automatic shut-off diesel nozzle
- 70lpm
- 1" F BSP swivel
- Spout OD 24mm



Piusibox Diesel Pump Kit

F00231000 (Basic) / F00231010 (Pro)

- 12v pump c/w 4m cable & clips in a sturdy, protective box
- Manual nozzle & 4m hose (Basic Kit)
- Manual nozzle, 6m hose, particle filter and gloves (Pro Kit)
- 45lpm (Basic) or 43lpm (Pro)

Self 3000 Diesel Nozzle

650000



- Manual nozzle
- 150 lpm
- 1" F BSP Swivel
- Max pressure 10 bar
- Diesel and Oil

Easyoil Oil Nozzle

966140

- Nozzle with flexi spout
- For oil filling operations in garages and workshops
- Max flow rate of 30lpm
- 1/2" F BSP



Oil Jugs & Funnels

- 180mm or 220mm ϕ funnels available
- 1ltr, 2ltr or 5ltr jugs available
- C/w caps and flexi-spouts



Viscomat 70 Oil Pump

334900

- 230v light oil transfer pump
- 1" F BSP inlet and outlet
- 25lpm
- For oil up to 500cSt



Rotary Fuel Hand Pump

CTS2001C

- For diesel and oil
- Max flow rate 22lpm
- 2" BSP drum fitting
- 25mm dispensing spout
- 1000mm 3 part rigid down tube

