

AGRIEPURE™ FG SERIES FUEL FILTERS



FLOW RATES & FILTER SIZES FROM 60 LPM TO 525LPM

The Agriepure™ FG Series Fuel Filters are available in a wide range of flow rates which are suitable to be fitted to Engines and Fuel Delivery Systems. Our FG-60 Filters are commonly used on engines that require high efficiency filtration, acceptable flow rates along with offering the ability for instant inspection of the fuel. Our FG-105 range offers a selection of filters ranging in flow rates from 60 to 525 litres per minute. Our filters separate free water and filter particulates down to 5 micron in size.



Features and Benefits:

- Suitable for Use with: **Diesel** | **Biodiesel** | **Petrol** | **Kerosene**
- Filtration: 5 micron (µm) & Water Separation
- 6x Sizes and Flow Rates Available
- Full Clear Bowl Assembly
- Installation on Suction or Pressure Side of pump
- 6 bar maximum working pressure
- Manual Drain Valve
- **OPTIONAL:** Pressure Gauge

Part Number	Max Flow LPM	Max Pressure	Port Size (BSP)	Installation	Height (mm)	Width (mm)	Depth (mm)	Weight (kg)
CD-FG-60	60	6 bar	3/4"	Suction or Pressure	260	150mm Dia.		2
CD-FG-105	105	6 bar	1"	Suction or Pressure	340	175mm Dia.		2.1
CD-FG105-210	210	6 bar	1 1/4"	Suction or Pressure	360	420	360	8
CD-FG105-315	315	6 bar	1 1/2"	Suction or Pressure	360	650	360	12
CD-FG105-420	420	6 bar	1 1/2"	Suction or Pressure	360	880	360	16
CD-FG105-525	525	6 bar	1 1/2"	Suction or Pressure	360	1110	360	20

Visit www.agriemach.com to view the complete range or call 01342 713 743 for more information.



Biodiesel

Petrol

Diesel

Kerosene

www.agriemach.com

Tel: (01342) 713 743
Fax: (01342) 719 181

Head Office: Wayfarers, Old Domewood, Copthorne, West Sussex, RH10 3HD

Warehouse: Unit 16 Horsted Square, Bellbrook Industrial Estate, Uckfield, East Sussex, TN22 1QG

